

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Version 8.6 Revision Date 22.03.2025 Print Date 23.03.2025

GENERIC EU MSDS - NO COUNTRY SPECIFIC DATA - NO OEL DATA

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Xylenes

Product Number : 247642 Brand : SIGALD

UFI : T632-765U-P99X-XSQ4

REACH No. :

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances Uses advised against : This product is not intended for consumer use.

1.3 Details of the supplier of the safety data sheet

Company :

1.4 Emergency telephone

Emergency Phone #: +(44)-870-8200418 (CHEMTREC (GB))

+(353)-19014670 (CHEMTREC Ireland) 001-803-017-9114 (CHEMTREC India)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Flammable liquids, (Category 3) H226: Flammable liquid and vapor.

Acute toxicity, (Category 4) H332: Harmful if inhaled.

Acute toxicity, (Category 4) H312: Harmful in contact with skin.

Skin irritation, (Category 2) H315: Causes skin irritation.

Eye irritation, (Category 2) H319: Causes serious eye irritation.

Specific target organ toxicity - single exposure, (Category 3),

Respiratory system

H335: May cause respiratory irritation.

Specific target organ toxicity - H373: May cause damage to organs

SIGALD- 247642 Page 1 of 15



repeated exposure, (Category 2),

hearing organs

through prolonged or repeated exposure.

Specific target organ toxicity - repeated exposure, (Category 2), Central nervous system, Liver,

Kidney

H373: May cause damage to organs

through prolonged or repeated exposure if

inhaled.

Aspiration hazard, (Category 1)

H304: May be fatal if swallowed and enters

airways.

Long-term (chronic) aquatic

hazard, (Category 3)

H412: Harmful to aquatic life with long

lasting effects.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram

Signal Word Danger

Hazard Statements

H226 Flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways. H312 + H332 Harmful in contact with skin or if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H335 May cause respiratory irritation.

H373 May cause damage to organs (hearing organs) through

prolonged or repeated exposure.

H373 May cause damage to organs (Central nervous system, Liver,

Kidney) through prolonged or repeated exposure if inhaled.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements

P210 Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face

protection.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water.

P331 Do NOT induce vomiting.

Supplemental Hazard

Statements

none

Reduced Labeling (<= 125 ml)

Pictogram

Signal Word Danger

Hazard Statements

H304 May be fatal if swallowed and enters airways.

SIGALD- 247642 Page 2 of 15



H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

Supplemental Hazard

Statements

none

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. Toxicological information:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Synonyms : Xylene mixture of isomers

Formula : C_8H_{10}

Molecular weight : 106.17 g/mol

Component		Classification	Concentration
Xylene			
CAS-No. EC-No. Index-No. Registration number	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32- XXXX	Flam. Liq. 3; Acute Tox. 4; Skin Irrit. 2; Eye Irrit. 2; STOT SE 3; STOT RE 2; Asp. Tox. 1; Aquatic Chronic 3; H226, H332, H312, H315, H319, H335, H373, H304, H412	>= 70 - < 90 %
ethylbenzene			
CAS-No.	100-41-4	Flam. Liq. 2; Acute Tox. 4;	>= 25 - < 30
EC-No.	202-849-4	STOT RE 2; Asp. Tox. 1;	%
Index-No.	601-023-00-4	Aquatic Chronic 3; H225,	
Registration	01-2119489370-35-	H332, H373, H304, H412	
number	XXXX		

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

SIGALD- 247642 Page 3 of 15



If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: caution if victim vomits. Risk of aspiration! Keep airways free. Pulmonary failure possible after aspiration of vomit. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2) Foam Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air at elevated temperatures.

Development of hazardous combustion gases or vapours possible in the event of fire.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

SIGALD- 247642 Page 4 of 15

A

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Storage class

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

8.2 Exposure controls

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact Material: Viton®

SIGALD- 247642 Page 5 of 15



Minimum layer thickness: 0.7 mm Break through time: 480 min

Material tested:Vitoject® (KCL 890 / Aldrich Z677698, Size M)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell,

Internet: www.kcl.de).

Full contact Material: Viton®

Minimum layer thickness: 0.7 mm Break through time: 480 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

Recommended Filter type: Filter A (acc. to DIN 3181) for vapours of organic

compounds

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Physical state clear, liquidb) Color colorless

c) Odor No data available

d) Melting Melting point/ range: 171 - 172 °C

point/freezing point

e) Initial boiling point 137 - 140 °C - lit. and boiling range

f) Flammability (solid, No data available

gas)

temperature

h) Flash point 25 °C - closed cup

i) Autoignition 463 °C at 1,013 hPa
 j) Decomposition No data available

k) pH substance/mixture is non-polar/aproticl) Viscosity Viscosity, kinematic: No data available

SIGALD- 247642 Page 6 of 15



Viscosity, dynamic: 0.76 mPa.s at 25.00 °C

m) Water solubility 0.1705 g/l at 25 °C - partly soluble

n) Partition coefficient: log Pow: 3.12 at 20 °C - Bioaccumulation is not expected.

n-octanol/water

o) Vapor pressure 23.99 hPa at 37.70 °C p) Density 0.86 g/mL at 25 °C - lit.

Relative vener No data available

q) Relative vapor

density

No data available

r) Particle

No data available

characteristics

s) Explosive properties Not classified as explosive.

t) Oxidizing properties none

9.2 Other safety information

Relative vapor density

3.67 - (Air = 1.0)

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapor/air-mixtures are explosive at intense warming.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Exothermic reaction with:

Strong oxidizing agents

Acids

sulfur

conc. sulfuric acid

Risk of explosion/exothermic reaction with:

Nitric acid

uranium hexafluoride

10.4 Conditions to avoid

Heating.

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

In the event of fire: see section 5

A

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Mixture

Acute toxicity

Symptoms: Irritations of mucous membranes in the mouth, pharynx, oesophagus and gastrointestinal tract.

Acute toxicity estimate Inhalation - 4 h - 12.25 mg/l - vapor(Calculation method)

Symptoms: Possible symptoms:, mucosal irritations, Cough, Shortness of breath, Possible

damages:, damage of respiratory tract

Acute toxicity estimate Dermal - 1,467 mg/kg

(Calculation method)

Skin corrosion/irritation

Remarks: Mixture causes skin irritation.

Serious eye damage/eye irritation

Remarks: Mixture causes serious eye irritation.

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Mixture may cause respiratory irritation.

Specific target organ toxicity - repeated exposure

Mixture may cause damage to organs through prolonged or repeated exposure.

- hearing organs

Mixture may cause damage to organs through prolonged or repeated exposure.

- Central nervous system, Liver, Kidney

Aspiration hazard

No data availableAspiration hazard, Aspiration may cause pulmonary edema and pneumonitis.

11.2 Additional Information

Endocrine disrupting properties

Product:

Assessment The substance/mixture does not contain

components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Other dangerous properties can not be excluded.

SIGALD- 247642 Page 8 of 15



Handle in accordance with good industrial hygiene and safety practice.

Components

Xylene

Acute toxicity

LD50 Oral - Rat - male - 3,523 mg/kg

(EC Directive 92/69/EEC B.1 Acute Toxicity (Oral))

Remarks: (ECHA)

Acute toxicity estimate Inhalation - 11.1 mg/l - vapor

(Expert judgment)

Acute toxicity estimate Dermal - 1,100.1 mg/kg

(Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table

3.1/3.2)

Skin corrosion/irritation

Skin - Rabbit

Result: Moderate skin irritation - 24 h

Remarks: (IUCLID)

Remarks: Drying-out effect resulting in rough and chapped skin.

After long-term exposure to the chemical:

Dermatitis

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Causes serious eye irritation. - 24 h

Remarks: (RTECS)

Respiratory or skin sensitization

Local lymph node assay (LLNA) - Mouse

Result: negative

(OECD Test Guideline 429)

Germ cell mutagenicity

Test Type: Mutagenicity (mammal cell test): chromosome aberration.

Test system: Chinese hamster ovary cells

Result: negative

Remarks: (National Toxicology Program)

Test Type: Ames test

Test system: Salmonella typhimurium

Result: negative

Test Type: sister chromatid exchange assay Test system: Chinese hamster ovary cells

Result: negative

Method: OECD Test Guideline 478 Species: Mouse - male and female

Result: negative

Carcinogenicity

No data available

Reproductive toxicity

No data available

SIGALD- 247642

Specific target organ toxicity - single exposure

May cause respiratory irritation. - Respiratory system

Page 9 of 15

Specific target organ toxicity - repeated exposure

Inhalation - May cause damage to organs through prolonged or repeated exposure.

- Central nervous system, Liver, Kidney

Aspiration hazard

May be fatal if swallowed and enters airways.

ethylbenzene

Acute toxicity

LD50 Oral - Rat - male and female - 3,500 mg/kg

Remarks: (ECHA)

LC50 Inhalation - Rat - male - 4 h - 17.8 mg/l - vapor

Remarks: (ECHA)

Acute toxicity estimate Inhalation - 17.8 mg/l - vapor

(ATE value derived from LD50/LC50 value) LD50 Dermal - Rabbit - 15,433 mg/kg

Remarks: (RTECS)

Skin corrosion/irritation

Remarks: Drying-out effect resulting in rough and chapped skin.

Dermatitis

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Mild eye irritation

Remarks: (ECHA)

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

Test Type: Chromosome aberration test in vitro Test system: Chinese hamster ovary cells

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: mouse lymphoma cells

Result: negative

Method: OECD Test Guideline 474 Species: Mouse - male - Bone marrow

Result: negative

Method: OECD Test Guideline 486 Species: Mouse - male and female

Result: negative

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

- hearing organs

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

SIGALD- 247642 Page 10 of 15

Aspiration hazard

Aspiration may cause pulmonary edema and pneumonitis.

SECTION 12: Ecological information

12.1 Toxicity

Mixture

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

Components

Xylene

Toxicity to fish static test LC50 - Oncorhynchus mykiss (rainbow trout) - 2.60

mg/l - 96 h

(OECD Test Guideline 203)

Toxicity to algae static test EC50 - Pseudokirchneriella subcapitata - 4.36 mg/l -

73 h

(OECD Test Guideline 201)

Toxicity to bacteria Remarks: (ECHA)

Toxicity to flow-through test NOEC - Oncorhynchus mykiss (rainbow trout)

fish(Chronic toxicity) - > 1.3 mg/l - 56 d

Remarks: (ECHA)

Toxicity to daphnia NOEC - Ceriodaphnia dubia (water flea) - 0.96 mg/l - 7 d and other aquatic (US-EPA)

invertebrates(Chronic

toxicity)

ethylbenzene

SIGALD- 247642 Page 11 of 15



Toxicity to fish semi-static test LC50 - Oncorhynchus mykiss (rainbow trout) -

4.2 mg/l - 96 h

(OECD Test Guideline 203)

Toxicity to daphnia

static test EC50 - Daphnia magna (Water flea) - 1.8 - 2.4 mg/l

and other aquatic invertebrates

- 48 h (US-EPA)

Toxicity to algae static test EC50 - Pseudokirchneriella subcapitata (green algae)

- 3.6 mg/l - 96 h

(US-EPA)

EC50 - Photobacterium phosphoreum - 9.68 mg/l - 30 min Toxicity to bacteria

Remarks: (IUCLID)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

No data available

SECTION 14: Transport information

14.1 UN number

IATA: 1993 IMDG: 1993 ADR/RID: 1993

14.2 UN proper shipping name

ADR/RID: FLAMMABLE LIQUID, N.O.S. (Xylene) FLAMMABLE LIQUID, N.O.S. (Xylene) IMDG: IATA: Flammable liquid, n.o.s. (Xylene)

14.3 Transport hazard class(es)

ADR/RID: 3 IMDG: 3 IATA: 3

14.4 Packaging group

ADR/RID: III IMDG: III IATA: III

14.5 Environmental hazards

ADR/RID: no IMDG Marine pollutant: no IATA: no

14.6 Special precautions for user

: No data available Further information

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SIGALD- 247642 Page 12 of 15



This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

Authorisations and/or restrictions on use

National legislation

Seveso III: Directive 2012/18/EU of the P5c FLAMMABLE LIQUIDS European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Other regulations

Observe work restrictions regarding maternity protection in accordance to Dir 92/85/EEC or stricter national regulations where applicable.

Take note of Dir 94/33/EC on the protection of young people at work.

15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out

SECTION 16: Other information

Full text of H-Statements

H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

SIGALD- 247642 Page 13 of 15



Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM -American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. -Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS -Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Classification of the	mixture	Classification procedure:
Flam. Liq.3	H226	Based on product data or assessment
Acute Tox.4	H332	Calculation method
Acute Tox.4	H312	Calculation method
Skin Irrit.2	H315	Calculation method
Eye Irrit.2	H319	Calculation method
STOT SE3	H335	Calculation method
STOT RE2	H373	Calculation method
STOT RE2	H373	Calculation method
Asp. Tox.1	H304	Calculation method
Aquatic Chronic3	H412	Calculation method

Further information

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture

SIGALD- 247642 Page 14 of 15



The life science business of Merck operates as MilliporeSigma in the US and Canada

and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

SIGALD- 247642 Page 15 of 15



The life science business of Merck operates as MilliporeSigma in the US and Canada